



# Exhaust System Hoses



## SOFTWALL MARINE EXHAUST HOSE Series 200

Type certified for wet exhaust service. Heavy wall construction with multiple plies of nylon spiral cord prevents shock, wall collapse, panting and vibration. Resists engine exhaust, high temperatures and ozone. Recommended for short, straight connections. Formulated to withstand operating temperatures of 220°F continuous. Color coded with blue strip brand. Meets SAE J2006 standard.

Part No.	I.D.	O.D.	Spiral Ply	Burst Pressure	Weight Per CFT
200-1120	1-1/2"	1-7/8"	2	200#	70
200-1580	1-5/8"	2"	2	175#	73
200-1340	1-3/4"	2-1/8"	2	175#	78
200-1780	1-7/8"	2-5/16"	2	160#	86
200-2000	2"	2-1/2"	2	160#	102
200-2180	2-1/8"	2-5/8"	2	200#	108
200-2140	2-1/4"	2-3/4"	2	190#	118
200-2380	2-3/8"	2-7/8"	2	260#	132
200-2120	2-1/2"	3"	2	260#	140
200-2580	2-5/8"	3-1/8"	2	230#	147
200-2340	2-3/4"	3-1/4"	2	220#	155
200-2780	2-7/8"	3-7/16"	2	220#	169
200-3000	3"	3-1/2"	2	220#	181
200-3180	3-1/8"	3-5/8"	4	200#	186
200-3120	3-1/2"	4"	4	190#	196
200-3340	3-3/4"	4-3/8"	4	180#	212
200-4000	4"	4-5/8"	4	170#	227
200-4180	4-1/8"	4-3/4"	4	150#	236
200-4120	4-1/2"	5-1/8"	4	250#	278
200-5000	5"	5-5/8"	4	230#	302
200-5180	5-1/8"	5-3/4"	4	210#	342
200-5120	5-1/2"	6-3/16"	4	200#	356
200-6000	6"	6-5/8"	4	190#	408
200-6580	6-5/8"	7-7/16"	4	170#	526
200-8000	8"	8-3/4"	4	160#	640
200-10000	10"	10-3/4"	4	150#	887
200-12000	12"	13"	4	150#	1,065
200-14000	14"	15"	4	125#	1,250

- Bulk pack: 12.5' length, 50' coil.
- Distributor pack: 6.25' and 12.5' poly tube.



## CORRUGATED MARINE EXHAUST HOSE Series 252

Same features as our Series 200 and 250 premium marine wet exhaust hose. Corrugated construction with double wire helix imbedded through multiple plies of tough rayon spiral cord provides strength and outstanding flexibility. For use on longer runs which require the tightest bends. Color coded with blue strip brand. Meets SAE J2006 standard.

## HARDWALL MARINE EXHAUST HOSE Series 250

Same features as our premium softwall exhaust hose. Wire reinforcement provides additional strength for longer connections with excellent flexibility. Recommended for runs longer than four times the inside diameter of the hose. Color coded with blue strip brand. Meets SAE J2006 standard.

Part No.	I.D.	O.D.	Spiral Ply	Burst Pressure	Weight Per CFT
250-1120	1-1/2"	1-13/16"	2	200#	62
250-1580	1-5/8"	1-15/16"	2	175#	67
250-1340	1-3/4"	2-1/16"	2	175#	71
250-1780	1-7/8"	2-3/16"	2	160#	76
250-2000	2"	2-3/8"	2	160#	81
250-2180	2-1/8"	2-7/16"	2	200#	87
250-2140	2-1/4"	2-5/8"	2	190#	91
250-2380	2-3/8"	2-3/4"	2	260#	96
250-2120	2-1/2"	3"	2	260#	106
250-2580	2-5/8"	3-1/8"	2	230#	116
250-2340	2-3/4"	3-1/4"	2	220#	127
250-2780	2-7/8"	3-3/8"	2	220#	142
250-3000	3"	3-1/2"	2	220#	144
250-3180	3-1/8"	3-5/8"	2	200#	151
250-3120	3-1/2"	4"	2	190#	173
250-4000	4"	4-9/16"	2	170#	210
250-4120	4-1/2"	5-1/16"	2	250#	251
250-5000	5"	5-5/8"	2	230#	292
250-6000	6"	6-5/8"	2	190#	376
250-8000	8"	8-7/8"	2	170#	480

- Bulk pack: 12.5' length, 50' coil.
- Distributor pack: 6.25' and 12.5' poly tube.

Part No.	I.D.	O.D.	Spiral Ply	Burst Pressure	Weight Per CFT
252-1120	1-1/2"	1-7/8"	2	200#	61
252-1580	1-5/8"	2"	2	175#	66
252-1340	1-3/4"	2-1/8"	2	175#	70
252-1780	1-7/8"	2-5/16"	2	160#	76
252-2000	2"	2-3/8"	2	160#	79
252-2380	2-3/8"	2-5/8"	2	260#	91
252-2120	2-1/2"	2-7/8"	2	260#	100
252-2780	2-7/8"	3-1/8"	2	220#	114
252-3000	3"	3-1/2"	2	220#	118
252-3180	3-1/8"	3-11/16"	2	200#	125
252-3120	3-1/2"	4"	2	190#	170
252-4000	4"	4-1/2"	2	170#	192
252-4180	4-1/8"	4-5/8"	2	150#	235
252-5000	5"	5-5/8"	2	230#	280
252-6000	6"	6-1/2"	2	190#	300
252-8000	8"	8-9/16"	2	170#	395

- Bulk pack: 12.5' length, 50' coil.
- Distributor pack: 6.25' and 12.5' poly tube.

