Fuel System Hoses





FUEL TANK FEED AND VENT HOSE USCG TYPE B1 AND B2 Series 315

Excellent quality standard fuel hose meets or exceeds all requirements of new ISO 7469 and SAE J1527. For use in non-enclosed engine compartments. Resistant to gasoline and alcohol-enhanced fuels. Braided reinforcement provides excellent flexibility and bend radius.

Part No.	I.D.	0.D.	Burst Pressure	Weight Per CFT	
TYPE B1 FUEL FEED					
315-0140	1/4"	1/2"	600#	9	
315-0560	5/16"	9/16"	600#	11	
315-0380	3/8"	5/8"	500#	13	
TYPE B2 FUEL VENT					
315-0580	5/8"	15/16"	400#	23	

- Bulk pack: 250' coil.
- Distributor pack: 10' poly bag, 25' and 50' payout box.



FUEL TANK FILL HOSE USCG TYPE A2 Series 350, 352 and 355

Premium quality fire-retardant fuel hose meets or exceeds all requirements of new ISO 7840 and SAE J1527 standards required by USCG, ABYC and NMMA. Resistant to gasoline, diesel and alcohol-enhanced fuels. Reinforced with helical wire between plies of nylon spiral cord. Provides strength and flexibility. Resistant to abrasion, heat and ozone.

Part No.	I.D.	0.D.	Spiral Ply	Burst Pressure	Weight Per CFT
HARDWALL					
350-1120	1-1/2"	1-7/8"	2	200#	67
350-1580	1-5/8"	2"	2	200#	79
350-1780	1-7/8"	2-3/8"	2	200#	93
350-2000	2"	2-1/2"	2	200#	107
350-2380	2-3/8"	2-7/8"	2	200#	124
CORRUGATED					
352-1120	1-1/2"	1-7/8"	2	200#	67
352-2000	2"	2-1/2"	2	200#	107
SOFTWALL					
355-1120	1-1/2"	1-15/16"	2	200#	75
355-2000	2"	2-9/16"	2	200#	110

- Bulk pack: 50' coil.
- Distributor pack: 10' and 12.5' payout box or poly tube.



FUEL TANK FEED AND VENT HOSE USCG TYPE A1 AND A2 Series 350

Premium quality fire-retardant fuel hose meets or exceeds all requirements of new ISO 7840 and SAE J1527 standards, recommended by USCG, ABYC and NMMA. Inner tube material provides extraordinary resistance to gasoline, diesel and alcohol-enhanced fuels. Braided reinforcement provides excellent flexibility and bend radius.

Part No.	I.D.	0.D.	working Pressure	weight Per CFT	Reel	
350-0140	1/4"	.618"	50#	16	250'	
350-0560	5/16"	.692"	50#	18	250'	
350-0380	3/8"	.763"	50#	21	250'	
350-0120	1/2"	.900"	45#	28	250'	
350-0580	5/8"	1.047"	45#	34	250'	
NON-BARRIER						
350-0340	3/4"	1.146"	40#	50	100'	
350-1000	1"	1.400"	40#	65	100'	

• Distributor pack: 10' poly bag, 25' and 50' payout box.



FUEL GRADE CLEAR PVC TUBING Series 155

Single extrusion clear PVC made with fuel and oilresistant materials. Typically used in non-regulated feed and distribution lines on personal watercraft or small jet powered boats.

Part No.	I.D.	0.D.	Working Pressure	Weight Per CFT	Bulk Coil
155-0180	1/8"	3/8"	70#	2	500'
155-0380	3/8"	9/16"	55#	6	500'

• Distributor pack: 50' payout box.

